

Model		EICON121-0 / CICON121-0	EICON122-0 / CICON122-0	EICON182-0 / CICON182-0	EICON242-0 / CICON242-0	
Climate type		1 TON 110V	1 TON 220V	1.5 TON	2 TON	
Power supply		Ph-V-Hz	1Ph-115V-60Hz	1Ph-208~230V-60Hz	1Ph-208~230V-60Hz	
Type			Cooling&Heating	Cooling&Heating	Cooling&Heating	
Power Supply Mode			alternating current	alternating current	alternating current	
Control type			Remote Controller	Remote Controller	Remote Controller	
Cooling	Capacity(T1/T3)	Btu/h	12000	12000	18000	24000
	Power Input(T1/T3)	W	1240	1240	1840	2300
	Rated Current(T1/T3)	A	10.8	5.64	8.40	10.5
	EER (T1/T3)	W/W	2.82	2.82	2.82	2.82
Heating	Capacity(T1/T3)	Btu/h	12000	12000	18000	24000
	Power Input(T1/T3)	W	1230	1230	1825	2280
	Rated Current(T1/T3)	A	10.7	5.6	8.30	10.4
	EER (T1/T3)	W/W	2.85	2.85	2.85	2.85
Compressor	Type		ROTARY	ROTARY	ROTARY	ROTARY
	Brand		GMCC	GMCC	Toshiba	Toshiba
Indoor unit	Indoor air flow	m3/h	550	550	850	1200
	Noise level	dB(A)	42	42	45	47
	Unit dimension (W*H*D)	mm	790X206X274	790X206X274	900X291X224	1025×240×320
	Packing (W*H*D)	mm	860×265×330	860×265×330	970×290×345	1105×315×405
Outdoor unit	Noise level	dB(A)	52	52	55	57
	Unit dimension (W*H*D)	mm	660*530*240	700*542*256	782*580*272	860*720*320
	Packing (W*H*D)	mm	785*600*340	820*600*340	905*640*365	1015*775*445
Refrigerant pipe	Refrigerant type		R410A	R410A	R410A	R410A
	Liquid side	mm	6	6	6	9.52
	Gas side	mm	9.52	12	12	15.88